



Our plain galvanised steel range is typically used for lighting applications, underfloor heating and other high temperature applications where continuous flexing is required.

Technical Details

Temperature Range: -50°C to +300°C

Material: Galvanised Steel

Colour: Self Coloured

Ingress Protection: IP40

Other Information: Low Fire Hazard, High Mechanical Strength, Highly Flexible, Manufactured to BS EN 61386

Product Code	Trade Size	Internal Diameter	External Diameter	Bending Radius	Coil Size
TB10-50M	10mm	7.0mm	9.0mm	23mm	50m
TB12-50M	12mm	10.0mm	13.0mm	25mm	50m
TB16-50M	16mm	13.0mm	16.0mm	33mm	50m
TB20-50M	20mm	17.0mm	20.5mm	38mm	50m
TB25-50M	25mm	21.0mm	25.0mm	45mm	50m
TB32-50M	32mm	28.5mm	32.0mm	55mm	50m
TB40-30M	40mm	37.5mm	41.5mm	62mm	30m
TB50-30M	50mm	48.5mm	53.0mm	110mm	30m
TB75-10M	75mm	78.5mm	85.5mm	160mm	10m
TB100-5M	100mm	102.0mm	109.0mm	210mm	5m

Nickel Plated Brass Fixed Fittings

- Material: Nickel Plated Brass
- 2 Part Fitting (Body & Shell)
- IP54



Product Code	Conduit Size	Thread Size	Pack Size
TCF10	10mm	M12 x 1.5mm	10
TCF12	12mm	M16 x 1.5mm	10
TCF16	16mm	M16 x 1.5mm	10
TCF16-20	16mm	M20 x 1.5mm	10
TCF20	20mm	M20 x 1.5mm	10
TCF25	25mm	M25 x 1.5mm	10
TCF32	32mm	M32 x 1.5mm	10
TCF40	40mm	M40 x 1.5mm	2
TCF50	50mm	M50 x 1.5mm	2
TCF75	75mm	3" PF	1
TCF100	100mm	4" PF	1

Nickel Plated Brass Swivel Fittings

- Material: Nickel Plated Brass
- 2 Part Fitting (Body & Shell)
- IP54



Product Code	Conduit Size	Thread Size	Pack Size
TCF10S	10mm	M12 x 1.5mm	10
TCF12S	12mm	M16 x 1.5mm	10
TCF16S	16mm	M16 x 1.5mm	10
TCF16-20S	16mm	M20 x 1.5mm	10
TCF20S	20mm	M20 x 1.5mm	10
TCF25S	25mm	M25 x 1.5mm	10
TCF32S	32mm	M32 x 1.5mm	10
TCF40S	40mm	M40 x 1.5mm	2
TCF50S	50mm	M50 x 1.5mm	2