



Technical Details

Material: Polypropylene

UV Resistant: Yes

UL 94 HB Self-extinguishing: 7mm, 10mm, 12mm & 16mm **Low**

Smoke Zero Halogen: 20mm, 25mm & 32mm **Halogen Free:**

40mm & 50mm

Color Options: Black, Red, blue, green, yellow, grey, white, orange

Product Code	Trade Size	Internal Diameter	External Diameter	Temperature Range	Fire Protection/ Halogen Free	Coil Size
TR07B-50M	7mm	6.9mm	9.9mm	-40°C to +125°C	UL 94 HB Self Exting.	50m
TR10B-50M	10mm	8.5mm	11.6mm	-40°C to +125°C	UL 94 HB Self Exting.	50m
TR12B-50M	12mm	10.1mm	12.7mm	-40°C to +125°C	UL 94 HB Self Exting.	50m
TR16B-100M	16mm	12.0mm	16.0mm	-15°C to +90°C	Halogen Free	100m
TR20B-100M	20mm	16.8mm	20.0mm	-40°C to +120°C	Low Smoke Zero Halogen	100m
TR25B-100M	25mm	19.9mm	25.0mm	-40°C to +120°C	Low Smoke Zero Halogen	100m
TR32B-50M	32mm	26.5mm	32.0mm	-40°C to +120°C	Low Smoke Zero Halogen	50m
TR40B-25M	40mm	31.0mm	40.0mm	-15°C to +90°C	Halogen Free	25m
TR50B-25M	50mm	39.0mm	50.0mm	-15°C to +90°C	Halogen Free	25m
TR63B-20M	63mm	56.3mm	67.2mm	-40°C to +110°C	Halogen Free	20m
TR75B-20M	75mm	66.5mm	80.0mm	-40°C to +110°C	Halogen Free	20m

Black Polypropylene Hinged Fittings

- Locknuts included
- Hinged/wrap around design
- IP40



Product Code	Conduit Size	Thread Size	Pack Size
TRF16B	16mm	M16 x 1.5mm	10
TRF20B	20mm	M20 x 1.5mm	10
TRF25B	25mm	M25 x 1.5mm	10
TRF32B	32mm	M32 x 1.5mm	10
TRF40B	40mm	M40 x 1.5mm	10
TRF50B	50mm	M50 x 1.5mm	10

Push-Fit IP65 Straight Fittings

- Locknuts included
- Push-fit design
- IP65



Product Code	Conduit Size	Thread Size	Pack Size
THF10-PG7	10mm	PG7	10
THF12B	12mm	M16 x 1.5mm	10
THF16B	16mm	M16 x 1.5mm	10
TRF20BPF	20mm	M20 x 1.5mm	10
TRF25BPF	25mm	M25 x 1.5mm	10